

NTLE-870

4' Track Pack with (3) MAC LED Track Heads

Source: 10W LED per head

700lm per head

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

Track pack comes complete and ready to install with mounting hardware and track heads. Components includes: (1) 4' single circuit track, (2) end caps, (1) floating canopy feed and (3) 700lm MAC LED track heads. The utilitarian style fits almost any design criteria.

FEATURES

- Over 75% energy savings when compared to incandescent
- 4' Track Pack includes all hardware and ready to install
- Black, silver or White finish
- 700lm / 10W LED output per head
- Field adjustable beam spreads (flood optic installed and spot included)
- 2700K, 3000K, 3500K or 4000K @ 90 CRI
- Dimmable
- Easily to longer lengths or additional track heads
- Perfect for multi family homes or apartments
- 5-Year Limited Warranty

CONSTRUCTION

Housing: Die-cast aluminum construction dissipates heat for longer life.

Adjustability: 350° horizontal and 90° vertical adjustment

ELECTRICAL

Input Voltage: 120V

Lumens / Wattage Per Head: 700lm / 10W

Color Temperature: 2700K, 3000K, 3500K or 4000K

CRI: 90

Beam Spread: 38° flood installed and 21° spot included

Lifetime: 44,000 hours @ L70

Dimming: ELV

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

One / Two Circuit Conversion: Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory, but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

LABELS AND LISTINGS

- cULus Listed for dry locations
- ENERGY STAR certified
- [5-Year Limited Warranty](#)



PRODUCT IMAGE



4' Track Pack with (3) MAC LED Track Heads

Series	Color Temperature / CRI	Finish
NTLE-870 = 4' Track Pack with (3) MAC LED Track Heads	927 = 2700K / 90 CRI	B = Black
	930 = 3000K / 90 CRI	S = Silver
	935 = 3500K / 90 CRI	W = White
	940 = 4000K / 90 CRI	

Example: **NTLE-870927B** = 4' Track Pack with (3) MAC LED Track Heads, 2700K / 90 CRI, Black Finish

PHOTOMETRICS

MAC LED Track Head

Type


Project

Catalog No.

Notes

Test Information

Test Number: NTT11030
Part Number: NTE-870L94010W
Beam Spread: 21° Spot
Lumens: 820lm
Wattage: 10.64W
Efficacy: 77lpw
CCT / CRI: 4000K / 90 CRI
Spacing Criteria (0°-180°): 0.38
Spacing Criteria (90°-270°): 0.38



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	192fc	1'-6"
6'	85.3fc	2'-4"
8'	48fc	3'-1"
10'	30.7fc	3'-10"
12'	21.3fc	4'-7"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	645	78.6
0-40	716	87.4
0-60	786	95.9
0-90	816	99.5
90-180	4	0.5
0-180	820	100

Candela Table

Vertical Angles	Candela
0	3071
5	2782
15	942
25	317
35	110
45	56

Test Information

Test Number: NTT11031
Part Number: NTE-870L94010W
Beam Spread: 38° Flood
Lumens: 846lm
Wattage: 10.94W
Efficacy: 77lpw
CCT / CRI: 4000K / 90 CRI
Spacing Criteria (0°-180°): 0.62
Spacing Criteria (90°-270°): 0.62



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	92.9fc	2'-8"
6'	41.3fc	4'-1"
8'	23.2fc	5'-5"
10'	14.9fc	6'-10"
12'	10.3fc	8'-1"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	599	70.8
0-40	707	83.6
0-60	805	95.1
0-90	842	99.5
90-180	5	0.5
0-180	847	100

Candela Table

Vertical Angles	Candela
0	1486
5	1413
15	944
25	441
35	179
45	70

Lumen Output Multipliers

Color Temperature: 2700K (0.87), 3000K (0.91), 4000K (1.00)