

NTM-716

6" Air-Tight Aluminum Shallow Baffle Cone Reflector

Type

Project

Catalog No.

Notes

CONSTRUCTION

Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare.

MOUNTING

Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Socket can be mounted directly to trim without bracket.

COMPATIBLE LAMP / HOUSINGS

50W R20/PAR20 Maximum (NHIC-27QAT, NHRIC-27QAT, NH-27Q, NHR-27Q, NFBIC-6INCATA)

60W A19 Maximum (NHIC-27QAT, NHRIC-27QAT, NH-27Q, NHR-27Q, NFBIC-6INCATA)

75W BR30/PAR30 Maximum (NHIC-27QAT, NHRIC-27QAT, NH-27Q, NHR-27Q, NFBIC-6INCATA)

90W R40/PAR38 Maximum (NFBIC-6INCATA)

LISTINGS

· cULus Listed for Damp Location when used with compatible housing




PRODUCT IMAGES AND DIMENSIONS



NTM-716BAL



NTM-716WAL



6" Air-Tight Aluminum Shallow Baffle Cone Reflector

Catalog No.

NTM-716BAL = 6" Black Air-Tight Aluminum Shallow Baffle Cone Reflector, White Flange

NTM-716WAL = 6" White Air-Tight Aluminum Shallow Baffle Cone Reflector, White Flange

Compatible Housings

Catalog No.

NHIC-27QAT = ICAT Shallow New Construction / 75W max.

NHRIC-27QAT = ICAT Shallow Remodel / 75W max.

NH-27QAT = Non-IC Shallow New Construction / 75W max.

NHR-27QAT = Non-IC Shallow Remodel / 75W max.

NFBIC-6INCATA = ICAT Fire Rated New Construction / 90W Max

Example: **NTM-716BAL** = 6" Black Air-Tight Aluminum Shallow Baffle Cone Reflector, White Flange