

NTS-26

6" Frosted Flat Lens with Specular Reflector

Type

Project

Catalog No.

Notes

FEATURES

Trim: High grade frosted flat lens attached to a metal trim. Precision spun 0.050 aluminum high grade specular clear reflector.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE LAMP / HOUSINGS

Line Voltage:

40W A19 Max. (NH-27Q; NHIC-17QAT; NHIC-27QAT; NHR-27Q; NHRIC-17QAT; NHRIC-27QAT)

60W A19 Maximum (NH-26Q; NHIC-17/100DWQA; NHR-26Q)

See individual housing specification sheets for more information.

LABELS AND LISTINGS

* cULus Listed for Wet Location when used with compatible housing



PRODUCT IMAGES & DIMENSIONS



6" Frosted Flat Lens with Specular Clear Reflector

Catalog No.

NTS-26 = 6" Frosted Flat Lens with Specular Clear Reflector and White Metal Trim

Compatible Housings

Catalog No.

NH-26Q = Non-IC New Construction / 60W max
NHR-26Q = Non-IC Remodel / 60W max
NHIC-17/100DWQA = IC Air-Tight Double Wall New Construction / 60W max
NHIC-17QAT = IC Air-Tight New Construction / 40W max
NHRIC-17QAT = IC Air-Tight Remodel / 40W max
NH-27Q = Shallow Non-IC New Construction / 40W max
NHR-27Q = Shallow Non-IC Remodel / 40W max
NHIC-27QAT = Shallow IC Air-Tight New Construction / 40W max
NHRIC-27QAT = Shallow IC Air-Tight Remodel / 40W max

Example: **NTS-26** = 6" Frosted Flat Lens with Specular Clear Reflector and White Metal Trim