

2" SLIM LIGHTS

SLIM2TRG-5CCT



HIGHLIGHTS

2" LED Regressed Gimbal Downlight - Compact, Adjustable Lighting With Sleek Design And Selectable CCT

- Durable aluminum body with adjustable gimbal
- Simple snap-in installation is fast and easy
- No housing required
- 30° tilting, 360° rotation
- Compatible with industry standard TRIAC/ELV dimmers (100-10%)
- Suitable for WET LOCATION

8W

120V AC

650 LMN

90Ra CRI

CERTIFICATIONS



COLOUR TEMPERATURE

2700K / 3000K / 3500K / 4000K / 5000K (Selectable)




SPECIFICATIONS

MODEL	SLIM2TRG-5CCT
Wattage	8W
Voltage	120V AC, 60Hz
Lumens	650 lmn
Beam Angle	38°
Lifetime	50,000 hours
Dimmable	Yes (TRIAC dimming)
CRI	90Ra
Rating	IC rated/Indoor use/ Wet Location
Grade of Protection	IP54
Cutout	Ø2-7/8" (72mm)
Operating Temperature	-20°C ~ +40°C

ELEVATE YOUR LIGHTING GAME

5 YEAR WARRANTY

DIMENSIONS



ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.



2" SLIM LIGHTS SLIM2TRG-5CCT

COLOUR OPTIONS




White



Black



CUT HOLE SIZE



INCLUDED IN BOX

- 1 x 2" Regressed Gimbal Downlight with Remote Driver



ACCESSORIES (SOLD SEPARATELY)



CORD-B24 | CORD-B120
Extension Cord




PLATE13-3 | PLATE13-3-L | PLATE26-3 | PLATE26-3-L
Construction plate made up of galvanized steel
for recessed lighting




PLATE3-HB
Galvanized steel mounting plate
with hanger bars



REFERENCE	QUANTITY	REMARKS	PROJECT DETAILS
			Project:
			Location:
			Architect:
			Engineer:
			Contractor:
			Submitted By:
			Date:

ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.

