

LINEAR STRIP LIGHTS SLST4-5CCT+WMS



HIGHLIGHTS

48" LED Linear Strip Light With Selectable CCT And Wattage, Along With Built-In Motion Sensor

- Daisy connection of up to 20 units per single power source running 347v
- Suspending installation and surface-mounted installation
- Diffused light, Damp location rated, Polycarbonate lens
- 5 year warranty



CERTIFICATIONS



COLOUR TEMPERATURE

3000K / 3500K / 4000K / 5000K / 6000K (Selectable)



SPECIFICATIONS

MODEL	SLST4-5CCT+WMS
Wattage	40W/50W/60W
Voltage	120-347V AC, 60Hz
Lumens	5200 lmn/6500 lmn/7800 lmn
Beam Angle	120°
Lifetime	50,000 hours
Dimmable	Yes (0-10v dimming)
CRI	80
Application	School/Hospital/Super Market/Office/Warehouse
Grade of Protection	IP20
Luminous Efficiency	130 LM/W
Operating Temperature	-20°C ~ +40°C
Case Quantities	8

LONG, LEAN AND LUMINOUS


5 YEAR WARRANTY

ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.




LINEAR STRIP LIGHTS SLST4-5CCT+WMS

DIMENSIONS




TESTING REPORT

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



CO PLANE ISOLUX DIAGRAM (UNIT:lx)




ACCESSORIES



DAISY CONNECTION

120V = 8 units
 277V = 16 units
 247V = 20 units



ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.



LINEAR STRIP LIGHTS SLST4-5CCT+WMS

MOTION SENSOR SETTINGS

By selecting the combination of the DIP switches, sensor will be precisely set for different applications.

1	
☒	100%
☐	50%

Detection area

In this area, movement will be detected and able to trigger the sensor. 100% detection area is also known as the strong sensitivity.

2	3	
☒	☒	5s
☒	☐	30s
☐	☒	1min
☐	☐	10min

Hold-time

The period of light keeping 100% brightness after moving objects leave the detection area.

4	5	
☒	☒	Disable
☒	☐	50lux
☐	☒	10lux
☐	☐	2lux

Daylight threshold

Definition of the ambient brightness; only when the ambient brightness is lower than the preset specific lux amount, the sensor will work; when it's preset as "disable", the sensor works every time it detects motion regardless the ambient brightness.

6	7	
☒	☒	0s
☒	☐	30s
☐	☒	20min
☐	☐	+ ∞


Stand-by period

The period of light keeping low output before it's completely switched off. When it's preset as "∞", the light always keep at low output if no movement in the detection area and doesn't turn off.


8	9	
☒	☒	10%
☒	☐	20%
☐	☒	30%
☐	☐	50%

Stand-by dimming level

The definition of low output in the standby period.



Operating voltage	10-15VDC
Stand-by power	<0.5W
Stand-by power	≤1W
Detection area	50%/100%
Hold time	5s/30s/1min/10min
Daylight threshold	2Lux/10Lux/50Lux/Disable
Stand-by period	0s/30s/20min/+∞
Stand-by dimming level	10%/20%/30%/50%
Microwave frequency	5.8GHz±75MHz
Microwave power	<1mW
Mounting height	Max. 4.5m/14.76ft (ceiling mounted)
Detection range	Max.ø12m/39.36ft (ceiling mounted)
Operating temperature	-20°C~+60°C
Detection angle	30°~150°
Motion detection	0.5~3m/s
IP rating	IP20
Warranty	5 years



REFERENCE	QUANTITY	REMARKS	PROJECT DETAILS
			Project:
			Location:
			Architect:
			Engineer:
			Contractor:
			Submitted By:
			Date:

ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.

