



RENO™
LIGHTING

Date:

Type:

Project Name:

Part Number:

LED FLOOD LIGHT



1/2" threaded nipple allows for easy installation to weather proof boxes or landscape mounting posts



DESCRIPTION

Reno compact flood lights are water resistant rated at IP65. Creating bright, security and spot lighting for a variety of applications such as perimeter, entryway, facades, landscapes, retail and residential complexes and architectural lighting. Can mount in almost any angle with a yoke-style arm and half-inch NPT threaded nipple

FEATURES

- Die-cast aluminum housing with Glass Lens
- (prevent yellowing)
- L70 rated chip for over 100,000 projected life hours
- 1/2" NPT stainless steel threaded nipple
- Dual Voltage 120-347V
- -40°C~ to 50°C operating temperature
- 5 Year Warranty
- Custom colours available

APPLICATIONS

- Parking Area
- Station
- Warehouse

SPECIFICATION


ORDER #	MODEL#	WATTS	VOLTAGE(V)	BEAM ANGLE	INITIAL LUMENS	CCT	CRI
R54001	RENO-FL-40W-D4-4K	40W	120-347V	T3	5250	4000K	74
R54002	RENO-FL-40W-D4-5K	40W	120-347V	T3	5250	5000K	70
R54003	RENO-FL-60W-D4-4K	60W	120-347V	T3	7350	4000K	74
R54004	RENO-FL-60W-D4-5K	60W	120-347V	T3	7350	5000K	70

DIMENSION




LUMINOUS EMITTANCE

■ 40W



■ 60W



905-604-4666



info@renolighting.com



www.renolighting.com