

Project Name

Location

Prepared By



SATCO S18451

13T8/U1-G13/LED/835/DUAL

Notes

General

Status	Active
Watts	13
Fluorescent Equivalent	31
Volts	120V-277V
Ballast Type	Type A/B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	22.5
Finish	Frosted
CCT (Kelvin)	3500
Temperature	Neutral White
CRI	80
Lumens	1800
Beam Spread	160
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	U-Bend
Technology	LED

Electrical

Ballasting Requirements	Ballast required (Type A) or Ballast bypass (Type B)
Operating Frequency	50/60 Hz
Dimmable Down To	N/A
Dimming Type	N/A
Power Factor	0.9
Operating Temperature	-25C (-13F) to a maximum of +45C (+113F)

Physical

MOL	22.59
MOD	1
Leg Spacing	1.63
Lens Finish	White
Lens Material	Plastic
Housing Color	White

Additional Information

Warranty	5 Year Limited
----------	----------------

Compliance

Safety Listing	cULus Listed for Type A; cULus Classified for Type B
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLNGZPZ9UOHF
CEC Status	Lawful for sale in California
RoHS Compliant	Yes

FCC Compliant	Yes
NSF Approved	No - Not Approved