



S29717

25T5/LED/46-835/BP/HO/120-277V
25 watt T5 LED; Miniature bi-pin base; 3500K; 50000 Average
rated hours; 3200 lumens; 120-277 volts

Features

- No ballast or external driver required
- All glass tube
- PET“shatterproof coated
- NSF Approved
- Single ended wiring



S29717

Item Number	UPC	Voltage	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base
S29717	045923297175	120-277	25	50/60Hz	T5	Miniature Bi-Pin	G5

Lamp Code	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
25T5/LED/46-835/BP/HO/120-277V	Frosted	48"	0.88"	3200	50000	3500	Neutral White

CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status	DLC ID:	RoHS Compliant	UL or ETL Listed
83	240	-20C (-4F) to a maximum of +45C (+113F)	25	Lawful for sale in California	PL3RGVA3G1QP DLC Search	Yes	Yes

UL Classification						Warranty	
cULus Classified - Damp Location Rated						5 Year Limited	



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051