



S29976

15T8/LED/48-835/DR
15 watt T8 LED; Medium bi-pin base; 3500K; 50000 Average
rated hours; 2100 lumens



Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Ballast required
- Solid State LED lighting
- High efficacy
- DLC Listed
- Compatible with emergency ballasts*
- All glass tube

S29976

*May not be compatible with all rapid start and emergency ballasts.

Ballast required

View:

[Ballast Compatibility Chart](#)

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S29976	045923299766	15	25W-32W	T8	Medium Bi-Pin	G13	15T8/LED/48-835/DR
Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
Non-Dimmable	Gloss White	48"	1.00"	2100	50000	3500	Neutral White
CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:	RoHS Compliant
82	210	-20C (-4F) to a maximum of +45C (+113F)	10	Box	Lawful for sale in California	PL5QTGX6T5Q2 DLC Search	Yes

UL or ETL Listed	UL Classification	Warranty
Yes	cULus - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051