

Project Name

Location

Prepared By



SATCO S9924

43T8/LED/96-840/BP/R17D HO

Notes

General

Status	Active
Watts	43
Fluorescent Equivalent	110
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Recessed Double Contact HO/VHO
ANSI Base	R17d
Nominal Length	96
Finish	Gloss White
CCT (Kelvin)	4000
Temperature	Cool White
CRI	82
Lumens	5500
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60 Hz
Dimmable Down To	N/A
Dimming Type	N/A
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical

MOL	96
MOD	1

Additional Information

Shatter-Proof Type	Yes
Installation Notes	Double ended wiring
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
NSF Approved	Yes - Approved