



LED LAMP

PURE VISION



PV-A19 (Base GU24)

Features & Benefits

Energy Star listed, Dimmable

15,000 hour average life


High CRI (80+)

Enclosed fixture application

Damp location approved

Beam angle 230°

Dimensional drawing



Warranty & Cautions

2-year limited warranty

Operating temperature range between -40°C and +40°C

UL/cUL listed, FCC compliant, RoHS compliant

Product Specification

ES	Model Number	Watts	Replacement Incandescent	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	Enclosed Fixture Application	Damp LOC.	M.O.L. (inch)	Case QTY.
Y	PV-A19/9.5W/27/D/GU	9.5	60W	GU24	120	15,000	230°	800	2700	80	Y	Y	4.17	40
Y	PV-A19/9.5W/30/D/GU	9.5	60W	GU24	120	15,000	230°	800	3000	80	Y	Y	4.17	40
Y	PV-A19/9.5W/40/D/GU	9.5	60W	GU24	120	15,000	230°	800	4000	80	Y	Y	4.17	40
Y	PV-A19/9.5W/50/D/GU	9.5	60W	GU24	120	15,000	230°	800	5000	80	Y	Y	4.17	40

Ordering Information

Example: PV-A19/9.5W/27/D/GU

LED CLASS	LAMP TYPE	WATTAGE	CCT(K)	Dimmable	Base
PV	A19	9.5W	27 (2700K)	D(Dimmable)	GU (GU24)

(Pure Vision)