

LED LAMP

PURE VISION



PV-T8DF



Features & Benefits

All glass construction	220° beam angle
Aluminium end caps	36,000 hour life (L70)
19W with 1800lm (NBF)	Instant on with no warm-up time
High CRI (82+)	Compatible with most Instant Start Ballast & Rapid Start Ballast ¹ with input voltage of 120-277V and 347V
Direct replacement for T8 linear fluorescent	

¹ For detail, you may contact your sales person or check www.turolight.com for ballast compatibility list

Dimensional drawing



Warranty & Cautions

5-year limited warranty for DLC listed lamps / 3-year limited warranty for non-DLC*

Bulb wall temperature range between -20°C and +45°C

Not recommended to use with ballast 5 years or older

*Please check the "Turolight LED Limited Warranty" for details

Product Specification

Ordering Code	Model Number	Nominal Lamp Power (Watts)	System Power (Watts)			Initial Lumen (lm)			Base	Hour Rating	Beam Angle	CCT(K)	CRI	M.O.L. (inch)	Case QTY.
			Low BF (0.78)	Normal BF (0.88)	High BF (1.16)	Low BF (0.78)	Normal BF (0.88)	High BF (1.16)							
1732409	PV-T8DF/15W/40/F	15	15	19	25	1400	1800	2500	G13	36,000	220	4000	82	48	25
1732506	PV-T8DF/15W/50/F	15	15	19	25	1400	1800	2500	G13	36,000	220	5000	82	48	25

Ordering Information

Example: PV-T8DF/15W/40/F

LED CLASS	LAMP TYPE	DIRECT FIT	WATTAGE	CCT(K)	FROST
PV	T8	DF	15W	40	F
				50	