

LED LAMP

VIVID Series



VIV-A15



Features & Benefits


5.5W replaces 40W incandescent
6W replaces 50W incandescent

High CRI (80+), dimmable

Enclosed fixture application for 5.5W

Damp location approved

Dimensional drawing



Warranty & Cautions

3-year limited warranty

Operating temperature range between -20°C and +40°C

UL/cUL listed, FCC compliant, RoHS compliant

Product Specification

Ordering Code	Energy Star	Model Number	Watts	Replacement Incandescent	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	Enclosed Fixture Application	Damp LOC.	M.O.L. (inch)	Case QTY.
1752105	Y	VIV-A15/5.5W/27/D/F	5.5	40W	E26	120	25,000	220°	450	2700	80	Y	Y	3.3	100
1752219	Y	VIV-A15/5.5W/30/D/F	5.5	40W	E26	120	25,000	220°	450	3000	80	Y	Y	3.3	100
1752420	Y	VIV-A15/5.5W/40/D/F	5.5	40W	E26	120	25,000	220°	450	4000	80	Y	Y	3.3	100
1752405	-	VIV-A15/6W/40/D/F	6	50W	E26	120	15,000	180°	500	4000	80	-	Y	3.3	50



Ordering Information

Example: VIV-A15/5.5W/27/D/F

LED CLASS	LAMP TYPE	WATTAGE	CCT(K)	DIMMABLE	FROST
VIV (Vivid)	A15	5.5W 6W	27 (2700K) 30 (3000K) 40 (4000K)	D (dimmable)	F (Frost)