



### Key Features

- 800 Lumens
- Suitable for enclosed fixtures and damp locations
- Dimmable
- Replaces 60W incandescent
- High CRI (80+)
- 25,000 hour average life
- Light weight design
- Even light distribution
- Reduces energy consumption up to 80%
- No UV, no infrared and mercury free

### Other information

- Operating temperature range between -20°C and +45°C
- UL/cUL listed, FCC compliant, RoHS compliant
- 3-year limited warranty in commercial and residential use



### Applications

- Hospitality
- Condominium
- Residential


### General Usage

- Table/Floor lamps
- Wall Scones
- Flush Mount
- Pendants

| Order Code | Model Number       | ES | Watts | Base | Volts | Hour Rating | Beam Angle | Initial Lumens | CCT (K) | CRI | EFA* | Damp Location | M.O.L. (inch) | Case Qty. |
|------------|--------------------|----|-------|------|-------|-------------|------------|----------------|---------|-----|------|---------------|---------------|-----------|
| 1762197    | VIV-A19/8W/27/D/GU |    | 8     | GU24 | 120   | 25,000      | 235°       | 800            | 2700    | 80  | Y    | Y             | 4.2           | 40        |
| 1762766    | VIV-A19/8W/30/D/GU |    | 8     | GU24 | 120   | 25,000      | 235°       | 800            | 3000    | 80  | Y    | Y             | 4.2           | 40        |
| 1762844    | VIV-A19/8W/40/D/GU |    | 8     | GU24 | 120   | 25,000      | 235°       | 800            | 4000    | 80  | Y    | Y             | 4.2           | 40        |
| 1762528    | VIV-A19/8W/50/D/GU | -  | 8     | GU24 | 120   | 25,000      | 235°       | 800            | 5000    | 80  | Y    | Y             | 4.2           | 40        |

\*Enclosed Fixture Application.

For the latest stock status please refer to your price list or send us an email at [sales@turolight.com](mailto:sales@turolight.com)



Dimensions



GU24 Base

How to read: VIV - A19 / 8W / 27 / D / GU  
 (LED Class) (Lamp Type) (Wattage) (CCT(K)) (Dimmable) (Base Type)

Distributed by: